

TRAVELER

DO NOT REMOVE FROM MACHINE

JOB NAME: _____

JOB CODE: _____

Order Date:	_____	Due Date:	8/8/2005
Financer:	_____	Model #	5T5-5-5-48TCxLxx
Voltage / Amps	230 volts/50 Amps	Serial #	DMS 1072
Spindle:	HSD ES 919	Configuration:	5 x 5 Twin Tbl, 48" Z
Controller:	Fagor 8055C	Tool Changer?	12 Position Carousel
Teach Pendant?	Yes	Shuttle Table?	NO
Inverter:	10 hp 230 Volt	Slip Ring?	NO
Transformer?	No	Auto Tool Length Set?	YES
Vacuum Pump?	No	Auto Lube System?	NO
DustChip Collector?	No	Tooling Package:	NO
Remote Station?	No		
Cold Air Gun?	No		

VACUUM TABLE 1-1/2" Aluminum Table, 3/8" Inserts 12" on Center

Motion: Lead Screw: Base: 40/40, 2 Qty @ 2464 mm
Lead Screw: Bridge: 40/40, 1 Qty @ 3848 mm
Lead Screw: Backbone: 32/20, 1 Qty @ 1507 mm
Rails: Base: Sz 35, 4 Qty @ 2794mm, T1=37mm Runner Blocks: 8 @ Sz 35
Rails: Bridge: Sz 35, 2 Qty @ 4000 mm, T1=40mm Runner Blocks: 4 Qty @ Sz 35
Rails: Backbone: Sz 35, 2 Qty @ 1726 mm, T1=23mm Runner Blocks: 4 Qty @ Sz 35

Soft Bellows: Bridge: 2 @ 146" Extended Length

Hard Bellows: Base 2 @ 98"
Backbone 1 @ 62"

Ship To: _____ Contact/Phone: _____

Machine Dimensions: 116" Wide x 175" Long x 153" Tall 12,000 lbs

Building Entry Restrictions: _____